




**IN-GROUND UPLIGHTER ADJUSTABLE 12W
UPLIGHT D180 LED 12W 830**

IN-GROUND

53415



Mounting sleeve



PRODUCT FEATURES:

- **Material:** high corrosion resistance die-cast copper-free aluminum body.
- **Adhesion of ISO class 1/ASTM class 4B high temperature painting**
- **Tempered safety glass.**
- **Stainless steel trim AISI 316**
- **Polypropilene housing for recess included**
- **Osram Led**
- **Led 12W**
- **Color temperature options 2000K 3000K,4000K,6000K,RGB 3in1, RGBW4in1**
- **Triac PWM 1-10V DALI (Dimming Option)**
- **Driver:Constant voltage input,constant current output**
- **Ingress Protectin Rating IP67**
- **Protection against impact IK10**
- **Dimensions Dia 160mm x H 122.5mm , Housing 148 x 154mm**
- **Warranty 5 years.**

IN-GROUND UPLIGHTER ADJUSTABLE 12W
UPLIGHT D180 LED 12W 830

IN-GROUND

53415

PRODUCT OVERVIEW

Ordering Code	53415
Product Name	IN-GROUND UPLIGHTER ADJUSTABLE 12W
Housing	High corrosion resistance die-cast copper-free aluminum body.
Diffuser	Tempered safety glass.
General Application	Outdoor (IP67)
Certification	CE, CB, TUV, Rohs, UKCA
Leds	Osram 6x2W
Fixture Luminous Flux (lm)	756lm 3000K
Luminaire Efficacy (lm/W)	63lm/w
Colour Temperature (K)	3000K (Available on request: 2000K,4000K,6000K,RGB 3in1, RGBW4in1)
Light Colour	Warm White
CRI (Ra)	Ra≥ 80
Colour Variation Initial (SDCM)	<3
Total Power Consumption (W)	12W
Main Voltage (V)	AC220-240V 50/60Hz
Electrical Protection	Class I
Dimmable	Non dimmable as standard.
IP rating	IP67
IK rating	IK10
Included Lamp	LED
Standard Driver	Standard On/Off
Operating Temperature °C	-20 to +50°C
Glow wire test ©	650°C
Dimensions	Dia: 160 H:122.5mm
Average life (Normal) h	>50,000 h @ L70/B50
Warranty	5 Years
Product EAN number	609670453415

LED colour option

2000K	10°/25°/45°/60°
3000K	10°/25°/45°/60°
4000K	10°/25°/45°/60°
6000K	10°/25°/45°/60°
RGB 3in1	10°/25°/45°/60°
RGBW4in1	10°/25°/45°/60°


Optional Accessory
Honeycomb-Louver
