

SMARTLUX TRACK LIGHT GALLERIA FOCAL

Track Light Zoomable Led -L40-3600LM-830-IP20

ACCENT LIGHTING

84402


Product Feature:

- Track mounted zoomable projector'
- The special zoomable optical system make Badu suitable for several different kind of application.
- The minimal and slim design make it suitable to match every kind of architectural style.
- The zooming smooth system by long pitch thread allows to change the beam angle from 15 to 60 degrees maintaining the projection clean.
- Available in on/off and dimmable version allow to solve complete projects also with smart controlling systems using a single typology of product.
- The soft spiral thread allows to adjust the bam light without to use any tool.
- Just turn by your hand the front clockwise or counterclockwise to set the desired beam angle of light.
- Good design and production with good materials and processes guarantee long life to the fixture making it stable in time.
- Luminaire body of die-cast aluminium. Ceiling ring powder-coated white (RAL 9016).
- Surface recessed track 3 circuit / Dali
- Beam angle 15-60°
- Reflector in specular silver anodized aluminium that can be easily replaced without using any tools.
- Light head pivot through 90° rotate through 355°
- Design, ideal for Shworooms, Hotels, Restaurants, Gallaris.
- Rendering: Ra >90, LED Chromacity: 3 step MacAdam ellipse, energy class: A++, A+, A,
- IR/UV free light source without heat radiation,
- operating voltage: 220-240V / 50-60Hz, electronic driver, electrical
- protection: CLASS I, ingress protection rating: IP20, suitable for internal environment
- Clean simple stylish appearance with aluminum housing - anti corrosion.
- COB LEDs from most reputed manufacturers with high luminous efficiency
- CCTO AVAILABLE 2700,3000K/4000K/6500K
- Anti-glare design soft non-dazzling for visual comfort achieving low glare control UGR<19.
- High efficiency yet soft & tender lighting effect with eco-friendly, No plution, No radiation and recyclable.
- Various dimming option protocols such as Triac, PWM,1-10V and Dali are also available upon request.
- High brightness, with ellipse MackAdams less than 3 ensuring Low SDCM <3 with minimal lumens depreciation along the years of operating, with standard CRI>90
- Designed with high end components , guaranteeing long life span > 50,000 hours @ L70/B10
- 5 year warranty.

SMARTLUX TRACK LIGHT GALLERIA FOCAL

Track Light Zoomable Led -L40-3600LM-830-IP20

ACCENT LIGHTING

84402



PRODUCT OVERVIEW

Item Code	84402
Product Name	Track Light Zoomable Led -L40-3600LM-830-IP20
Technology	LED
Housing	Die cast aluminium powder coated
Reflector	Direct lighting with low glare control UGR<19
General Application	Indoor
Adjustability	Rotation 355° / Tilt 90°
Beam Angle	15° - 60°
Certification	EU, CE, TUV, RoHs
Leds	COB
Fixture Luminous Flux (lm)	3600lm
Luminaire Efficacy (lm/W)	90lm/W
Colour Temperature (K)	3000K (2700,4000K 6500K) Upon Request
Light Colour	Warm White
CRI (Ra)	>90
Colour Variation Initial (SDCM)	<3
Photobiological Risk Group	RG0
Total Power Consumption (W)	40W
Main Voltage (V)	240V, 50/60HZ
Electrical Protection	Class III
Dimmable	All protocols are available upon request, Non-Dim On/Off, 1-10V, DALI
Colour (body/trim)	WHITE
IP rating	IP20
IK rating	02
Included Lamp	Integrated LED
Diffuser	High transmittance opal UV protected
Standard Driver	Electronic on/off non-dim with high power factor correction PFC > 0.95
Operating Temperature °C	-20 to +40
Glow wire test @	650°C
LOR (%)	1
Average life (Normal) h	>50,000 h, L70B10 @ 25°C.
Product EAN number	609670484402
Warranty	5 Years

